FagronLab[™] CC2A2 1100UV

Positive pressure workbench



The FagronLab[™] Class II Biological Safety Cabinet is specialized to provide environmental, product, and personnel protection. Special designed for pharmaceutical laboratories that work with pathogenic biological agents (PBA). Guarantees the protection of the personnel by an air curtain in the work opening which prevents any escape of the pathogens from the work chamber. Additionally, it guarantees environmental protection for biological safety with the use of two HEPA filters. The HEPA filtered downward laminar flow protects the material that is used inside the cabinet, and the exhaust HEPA filter protects the environment, since it ensures that the air passing through it is contaminant free. The FagronLab[™] CC2A2 cabinet is a new generation of safety cabinets which are easily installable in a laboratory.

- System with two HEPA filters for 70% air recycling and 30% export
- Set up functions on a readable LCD display with indicators for all operations. Operation panel and remote control
- Working area of 304 stainless steel surrounded by negative pressure. Removable for better cleaning
- Sterilization with UV lamp at 253.7nm for effective protection from contamination
- Internal LED lighting
- Glass opening front with anti-UV protection, controlled lifting with foot switch
- Optionally installed air outlet
- Made of stainless steel with antibacterial coating

Fagron Hellas

12 km N.R. Trikala - Larisa P.C. 42100, P.O. Box 32 Trikala, Greece T +30 24310 83633-5 F +30 24310 83615 www.fagron.gr

Technical Parameters

| Inflow Velocity | 0.53±0.025 m/s |
|------------------------|--|
| Down flow Velocity | 0.33±0.025 m/s |
| HEPA Filter | Two, 99.999% efficient at 0.3 um. Filter life indicator |
| Front Window | Motorized. Two-layer laminated toughened glass ≥ 5mm. Anti UV |
| UV Lamp | 30W*1 UV timer, UV life indicator, emis- sion of 253.7 nanometers for most efficient decontamination |
| Illuminating Lamp | 12W*2 LED Lamp |
| Airflow System | 70% air recirculation, 30% air exhaust |
| Noise | EN12469 ≤ 58 dB / NSF49 ≤ 61 dB |
| Consumption | ≤760W |
| Power Supply | AC220V±10%, 60/50Hz; 110V±10%, 60Hz |
| Work Surface Height | 750mm |
| Internal Size (WxDxH) | 940x600x660 mm |
| External Size (WxDxH) | 1100x750x2250 mm |
| Packaging Size (WxDxH) | 1220x1000x1840 mm |
| Gross Weight | 243 kg |
| | |

